



Pos.	Size		Article code	Dimensions				Electrical parameters
	IEC	Wistro		A*	B*	D*	D1	
1.	160	BG112	15.51.0433 A	125	235	250	219	87W; 3-phase 346÷525V; 0,20A 64W; 1-phase 230÷277V; 0,27A
2.	180		15.51.0433 B		252	265		
3.	200	BG132	15.51.0398 A	140	278	288	258	160W; 3-phase 346÷525V; 0,37A 125W; 1-phase 230÷277V; 0,52A
4.	225		15.51.0398 B		302	315		
5.	250		15.51.0398 B					
6.	280/315	BG160	15.51.0396 A	160	345	364	311	314W; 3-phase 346÷525V; 0,74A 246W; 1-phase 230÷277V; 1,05A
7.	315		15.51.0396 B		380	400		
8.	355	BG200	15.50.0516 A	200	406	420	385	154W; 3-phase 346÷525V; 0,31A
9.	355	BG250	15.50.0515 A	205	496	510	480	254W; 3-phase 346÷525V; 0,42A
10.	400/450		15.50.0515 B		585	600		

Notes:

* - other dimensions are possible

Edition 1 - 2022

wistro

FORCED VENTILATION UNITS FOR ELECTRIC MOTORS